

**Crown® Latex Agent® Oil Bond®** - CR.LAOB - September 6, 2024**Description**

CROWN® Latex Agent® Oil Bond® is a truly unique water based, low VOC product. Oil Bond is designed and formulated to work in all latex paint. Oil Bond is first wiped on oil or water-based paint, varnish, lacquer, polyurethane or even powder coated items with a clean, lint free rag. Oil Bond contains cleaning surfactants, deglossing agents and priming, one part, self-crosslinking resins. The product will then clean, degloss and pre-prime painted surfaces, most clear coat surfaces (not laminates or plastics) and most powder coated surfaces (not automotive, clear coat finishes).

Prominent Features

- Paint latex over previously painted oil or polyurethane surfaces without
- Eliminates the need for sanding or priming.
- Great for use on cabinets, trim, furniture and doors.

Uses

- Painting over oil-based surfaces without the need for priming or sanding.

Limitations

- Do not use in clear varnishes.
- Do not add FLOETROL® to oil or alkyd-based paints. For these paints use OWATROL® OIL*

Application

Carefully read all cautions and instructions before use. Protect hands with solvent-resistant gloves, and eyes with safety glasses. Open can slowly to relieve pressure. When using product apply to one small area at a time not to exceed three square feet as the danger for fire and health effects increases dramatically when used over large areas.

Disposal

The generation of waste should be avoided or minimized whenever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Storage

Store in dry, cool, well-ventilated areas away from strong oxidizing agents, strong bases, food, and drink. Keep from freezing. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children.

Packaging

1 Quart – 6 per case - 'F' style plastic container