

**Crown® Acetone** - CR.AC - January 17, 2024**Description**

CROWN® Acetone is a very strong, fast evaporating solvent used professionally for thinning and cleaning fiberglass resins, epoxies, vinyls, lacquers, and adhesives. Effective clean-up solvent for fiberglass projects. An excellent heavy-duty degreasing agent and cleaner.

**Prominent Features**

- 100% pure acetone.
- Superior-quality solvent for resins, epoxies, vinyls, lacquers, and adhesives.
- Effective clean-up for fiberglass projects.
- Excellent heavy-duty degreasing agent.
- Fast evaporation rate.

**Uses**

- Degreaser and remover for specified resins, inks, adhesives and contact cements.
- Use in boat repair and fiberglass projects.

**Limitations**

Do not use as a general-purpose cleaner. Acetone may soften or damage plastics, synthetics and many other finishes.

**Application**

Carefully read all cautions and instructions before use. Protect hands with solvent-resistant gloves, and eyes with safety glasses. Open can slowly to relieve pressure. When using product apply to one small area at a time not to exceed three square feet as the danger for fire and health effects increases dramatically when used over large areas.

**Disposal**

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products.

**Storage**

Store in dry, cool, well-ventilated areas away from strong oxidizing agents, strong acids, perchlorates, aliphatic amines, chromyl chloride, hexachloromelamine, chromic anhydride, potassium tertbutoxide, halogens, rubber, and various plastics, food, and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children.

**Packaging**

1 Quart – 6 per case - 'F' style metal container  
1 Gallon – 4 per case - 'F' style metal container  
5 Gallon – Single units - metal pail container  
55 Gallon – Single units - metal drum container