

**Crown® Japan Drier** - CR.JD - February 20, 2024

| | |
|---------------------------|--|
| Description | CROWN® Japan Drier is a special blend of lead-free drying agents that accelerates the drying ability of oil-based paint and varnish. This product speeds the drying time between coats of finish, even in damp or cool weather. Use this product with oil-based paints, oil-based enamels and varnishes. |
| Prominent Features | <ul style="list-style-type: none">• Lead-free.• Accelerates the drying ability of oil-based paints and varnishes.• Speeds the drying time between coats, even in damp or cooler weather. |
| Uses | <ul style="list-style-type: none">• Accelerating drying time of oil-based paints and varnishes. |
| Limitations | Do not use with latex paint, water-based finishes, lacquer polyurethane or other synthetic finishes. |
| Application | Use 2 to 4 ounces per gallon of paint or varnish to speed the drying time between application coats of finish when the weather is damp or cool. Use this product with oil-based paints, enamels and varnish. Carefully read all cautions and instructions before use. Protect hands with solvent-resistant gloves, and eyes with safety glasses. Open can slowly to relieve pressure. When using product apply to one small area at a time not to exceed three square feet as the danger for fire and health effects increases dramatically when used over large areas. |
| Disposal | Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products. |
| Storage | Store in dry, cool, well-ventilated areas away from strong oxidizing agents, food, and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children. |
| Packaging | 1 Quart – 6 per case - 'F' style metal container |