

**Crown® Toluol (Toluene)** - CR.TO - February 15, 2024

Description	CROWN® Toluol (Toluene) is a fast-drying solvent used for thinning paints, enamels, varnishes and alkyd resins. Often specified as a thinner for specialty paint and coatings.
Prominent Features	<ul style="list-style-type: none">• Fast-drying solvent.• Thins paint, enamels, varnishes, & alkyd resins.• Similar to Xylene, but faster evaporation rate.
Uses	<ul style="list-style-type: none">• Thinner for certain synthetic enamels, varnishes and alkyd resins.• Often specified as a thinner for specialty paint and coatings.
Limitations	Overthinning will cause paints to become brittle and appear flat.
Application	Carefully read all cautions and instructions before use. Protect hands with solvent-resistant gloves, and eyes with safety glasses. Open can slowly to relieve pressure. When using product apply to one small area at a time not to exceed three square feet as the danger for fire and health effects increases dramatically when used over large areas.
Disposal	Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products.
Storage	Store in dry, cool, well-ventilated areas away from strong oxidizing agents, strong acids, nitric acid, sulfuric acid, rubber, various plastics, food, and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children.
Packaging	1 Gallon – 4 per case - 'F' style metal container 5 Gallon – Single units - metal pail container 55 Gallon – Single units - metal drum container