

**Crown® Extra Strength Paint Thinner (Substitute) South Coast AQMD - CL.LVPTSSC - April 15, 2024**

Description	Crown® VOC Compliant Extra Strength Paint Thinner Substitute is specifically designed for the paint professional seeking a professional-grade alternative to traditional Paint Thinner.
Prominent Features	<ul style="list-style-type: none">• Extra-strength, acetone-based cleaner for painting equipment.• Fast evaporating thinner for oil-based products.• Comparable evaporation rate to Toluene and MEK.• Effective cleaner on brushes, rollers and trays.• VOC Compliant.
Uses	Cleaner for brushes & rollers and spray equipment for oil-based products.
Limitations	Not recommended for use in spray equipment. Do not use to clean, flush or soak spray equipment.
Application	To clean and prep surfaces, add Crown® VOC Compliant Extra Strength Paint Thinner Substitute to a cotton cloth and wipe. Refer to coating manufacturer's instructions before thinning. Do not use more than recommended (no more than 15%). Always test a small amount of this product before use to verify compatibility. Stir thinner into coating gradually until a uniform consistency is achieved. Not recommended for use in spray equipment. Do not use to clean, flush or soak spray equipment. If a faster evaporation rate is desired, use Crown® VOC Compliant Lacquer Thinner. Can also be used for cleaning brushes. Note: This product has a faster evaporation rate and is stronger than traditional Paint Thinner.
Disposal	Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products.
Storage	Store in dry, cool, well-ventilated areas away from incompatible materials strong oxidizing agents, strong acids, strong bases, perchlorates, aliphatic amines, halogens, potassium t-butoxide, rubber, various plastics, food, and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residues. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Do not take internally. Keep out of reach of children.
Packaging	1 Gallon – 4 per case - 'F' style metal container