

**Crown® Pro Thinner** - CL.PRTM25 - January 19, 2024

Description	CROWN® VOC Compliant Pro Thinner is a professional grade, specialty thinner with comparable evaporation rate to Toluene & Methyl Ethyl Ketone (MEK).
Prominent Features	<ul style="list-style-type: none">• Replaces Toluene and MEK.• Strong cleaner for wood and metal surfaces.• Maximum solvency for thinning Alkyd Paints, Enamels, Varnishes, Epoxies & Polyurethanes.
Uses	<ul style="list-style-type: none">• Thinner for Alkyd Paints, Enamels, Varnishes, Epoxies & Polyurethanes.• Strong cleaner for wood and metal surfaces.
Limitations	Do not use as a general-purpose cleaner. Pro Thinner may soften or damage plastics, synthetics and many other finishes.
Application	Carefully read all cautions and instructions before use. Protect hands with Refer to coating manufacturer's instructions before thinning. Always test a small amount of this product in the coating before use to verify compatibility. Stir thinner into coating gradually until a uniform consistency is achieved. For best results, thin coatings no more than 20%. To prep and clean surfaces, add thinner to a cotton cloth and wipe. Do not use to clean or flush spray equipment. Note: if a faster evaporation rate is desired, use Crown® VOC Compliant Lacquer Thinner.
Disposal	Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products.
Storage	Store in dry, cool, well-ventilated areas away from strong oxidizing agents, strong acids, strong bases, perchlorates, aliphatic amines, halogens, potassium t-butoxide, rubber, and various plastics, food, and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Do not take internally. Keep out of reach of children.
Packaging	1 Quart – 6 per case - 'F' style metal container 1 Gallon – 4 per case - 'F' style metal container 5 Gallon – Single units - metal pail container