

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: Crown Lacquer Thinner 25

SDS number: CR.LT25

Synonym(s): Solvent blend

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Solvent, thinner

Uses advised against: None specified

1.3 Details of the supplier and of the safety data sheet

Manufacturer/Distributor

SolvChem Consumer Products

1904 Mykawa Road

Pearland, TX 77581-3210 USA

1-281-485-1458

1.4 Emergency telephone number

CHEMTREC: 1-800-424-9300 (USA)

CANUTEC: 1-613-996-6666 (Canada)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification in accordance with 29 CFR 1910 (OSHA HCS) and Regulation EC No. 1272/2008

Flammable Liquid - Category 2 [H225]

Acute Toxicity, Oral - Category 3 [H301]

Aspiration Hazard - Category 1 [H304]

Acute Toxicity, Dermal - Category 3 [H311]

Skin Irritation - Category 2 [H315]

Eye Irritation - Category 2A [H319]

Acute Toxicity, Inhalation - Category 3 [H331]

Single Target Organ Toxicity, Single Exposure - Category 3; STOT SE 3 [H336]

Reproductive Toxicity - Category 2 [H361fd]

Single Target Organ Toxicity, Single Exposure - Category 1; STOT SE 2 [H370]

Single Target Organ Toxicity, Repeated Exposure - Category 2; STOT RE 2 [H373]

Aquatic Toxicity, Chronic - Category 2 [H411]

2.2 Label elements

Hazard symbol(s):



GHS02



GHS06



GHS07



GHS08



GHS09

Signal word:

Danger

Hazard statement(s):

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

H361fd - Suspected of damaging fertility and the unborn child

H370 - May cause damage to the central nervous system, the optic nerve, the liver and kidneys

H373 - May cause damage to the central nervous system, liver and kidneys through prolonged and repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements

[Prevention]

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, open flames and hot surface. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 + P242 - Use explosion proof electrical, ventilating and lighting equipment. Use only non-sparking tools.

[Response]

P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist or vapor.
P264 - Wash hands and other exposed skin areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing and eye protection.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER or doctor.
P303 + P361 + P353 - IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340 + P311 - IF INHALED: Remove victim to fresh air and keep at rest in a comfortable position for breathing. Call a POISON CENTER or doctor.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 - If exposed or concerned: Get medical attention.
P321 - Specific treatment: Seek medical attention or call a POISON CENTER. Refer to Section 4 of this SDS.
P332 + P337 + P313 - If skin irritation occurs or if eye irritation persists: Get medical attention.
P361 + P363 - Take off immediately contaminated clothing and wash before reuse.
P370 + P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P391 - Collect spillage.
P405 + P403 + P233 + P235 - Store locked up in a well-ventilated place. Keep container tightly closed. Keep cool.
P501 - Dispose of contents and containers in accordance with national and local regulations.

[Storage]

[Disposal]

2.3 Classification of substance or mixture

Repeated exposure may cause skin dryness or cracking

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

% by Weight	Ingredient	CAS Number	EC Number	Index Number	GHS Classification
35 - 55	Methanol	67-56-1	200-659-6	607-021-00-X	H225, H301, H311, H331, H370
23 - 43	Distillates (petroleum), hydrotreated light, low boiling	68410-97-9	270-093-2	649-332-00-3	H225, H304, H315, H336, H361fd, H411
10 - 23	Acetone	67-64-1	200-662-2	606-001-00-8	H225, H319, H336
0.5 - 3	Toluene	108-88-3	203-625-9	601-021-00-3	H225, H304, H315, H336, H361d, H373
0.1 - 3	2-Butoxyethanol	111-76-2	203-905-0	603-014-00-0	H227, H302, H312, H315, H319, H332

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with the applicable provisions of paragraph (i).

There are no additional ingredients present in this product which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4 – FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation: If product mist or vapor causes respiratory irritation or distress, move the exposed person to fresh air immediately. If breathing is difficult or irregular, administer oxygen; if respiratory arrest occurs, start artificial respiration by trained personnel. If unconscious, maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If symptoms persist or if the victim feels unwell, seek medical attention.

Eyes: Immediately flush eyes with large amounts of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses, if present and easy to do, after first 2 minutes and continue rinsing. If irritation persists seek medical attention, preferably from an ophthalmologist.

Skin: Flush skin with large amounts of water while removing contaminated clothing. Wash the affected area with soap and water followed by thorough rinsing. Wash contaminated clothing and shoes before reuse. If irritation persists or if the victim feels unwell, seek medical attention.

Ingestion: Rinse mouth with water if the victim is conscious. Remove dentures if present. DO NOT induce vomiting unless directed to do so by medical personnel. Vomiting may occur spontaneously. To prevent aspiration of material into the lungs, lay the victim on one side with the head lower than the waist. Never give anything by mouth to an unconscious or convulsing person. Do not leave the victim unattended. Seek immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Potential health symptoms and effects

Eyes: Causes serious eye irritation with inflammation, swelling, pain and tearing. Risk of corneal clouding or corneal injury. May cause painful sensitization to light. Prolonged exposure may cause lesions. Vapor or mist may cause eye irritation.

Skin: Toxic if absorbed through the skin. May cause skin irritation with localized redness, itching and discomfort. Prolonged contact with unprotected skin may cause drying and cracking of the skin and/or dermatitis.

Inhalation: Toxic if inhaled. May cause respiratory tract irritation with headache, cough and shortness of breath. May cause salivation, nausea, vomiting, drowsiness, dizziness, anesthetic effects, narcosis, fatigue, cyanosis, apnea and cardiac arrest. May cause central nervous system depression and other central nervous system effects, including incoordination, impaired reaction time, performance and speech impairment, encephalopathy (characterized by altered mental status, memory loss and visual problems), unconsciousness, coma and death. Lung irritation lead to chemical pneumonitis and pulmonary edema.

Ingestion: Toxic if swallowed. Causes irritation of the digestive tract with nausea, vomiting, abdominal pain and diarrhea. Causes dizziness, drowsiness, weakness, fatigue, headache and unconsciousness. May cause central nervous system depression with effects similar to those of acute inhalation. May cause liver and kidney damage. This material can get into the lungs during swallowing or vomiting causing lung inflammation and chemical pneumonitis, which may be fatal. Symptoms of aspiration into the lungs include coughing, gasping, choking, shortness of breath, bluish colored skin, rapid breathing and rapid heart rate.

Chronic: Prolonged or repeated skin contact may cause defatting of the skin, dermatitis or aggravate existing skin conditions. Chronic inhalation, skin absorption or ingestion can cause hemolysis, changes in liver function, kidneys and central nervous system with symptoms parallel to acute inhalation. Chronic exposure may cause impaired eyesight or blindness, breathing difficulties, confusion, dizziness, apprehension, memory loss, headache, tremors, weakness, anorexia, nausea, tinnitus, irritability, thirst, liver damage, kidney impairment and blood disorders. Impaired central nervous system functions from pre-existing disorders may be aggravated by exposure to this product. Effects may be delayed. Toluene is a possible human carcinogen. Effects may be delayed. Exposure to this product may damage fertility or the unborn child. Refer to Section 11.2.

Reports have associated repeated and prolonged occupational exposure to light petroleum products with irreversible brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Advice to doctor and hospital personnel

Administration of adsorbents such as activated charcoal may be of value. Gastric lavage may be effective when performed by a physician within 4 hours of ingestion. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable methods of extinction: Use extinguishing media such as water spray or fog, carbon dioxide, foam and dry chemical.

Unsuitable methods of extinction: Water jets or streams may spread the fire.

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapor! Vapors are heavier than air and can travel along the ground to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Exposure to ignition sources (e.g. cell phones) can ignite vapors, causing a flash fire. Closed containers may explode due to the buildup of pressure when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent or may be delayed. Obtain medical attention.

Explosion hazards: Avoid sources of ignition. Vapors may form an explosive mixture with air, especially in confined spaces. Ground and bond containers in storage and when container is in use.

5.3 Advice to firefighters

Firefighters should wear full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. *Be aware that burning liquid may float on water.* Firefighters must control runoff to prevent environmental contamination. Notify appropriate authorities of potential fire and explosion hazard if liquid enters sewers or waterways.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate non-essential personnel. Wear appropriate protective clothing and equipment designated in Section 8.2. Ventilate the area. Remove all sources of ignition. NO SMOKING. Clean up spills immediately. Spills create a slip hazard.

6.2 Environmental precautions

Avoid dispersal of spilled material or runoff and prevent contact with soil and entry into drains, sewers or waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements.

6.3 Methods and materials for containment and cleaning up

Approach spill from upwind direction. DO NOT FLUSH SPILL DOWN THE DRAIN. Cover drains and contain spill. Cover spill with a large quantity of inert absorbent. Do not use combustible material such as sawdust. Collect material using non-sparking tools and place into an approved container for proper disposal. Observe possible material restrictions (Sections 7.2 and 10.5). Do not allow material or runoff from rinsing contaminated areas to enter floor drains or storm drains and ditches that lead to waterways. Dispose of contents and containers via a licensed waste disposal contractor.

If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal in accordance with local regulations.

Distillates (petroleum), hydrotreated light, low boiling are classified as oil under Section 311 of the Clean Water Act (CWA) and under the Oil

Pollution Act (OPA). In the USA discharges or spills of material on waters of the United States, their adjoining shorelines or into conduits leading to surface waters must be reported to the National Response Center at 800-424-8802.

6.4 Reference to other sections

For indications about waste treatment, see Section 13.

SECTION 7 – STORAGE AND HANDLING

7.1 Precautions for safe handling

Wear all appropriate personal protective equipment specified in Section 8.2. Do not get in eyes or on skin or clothing. Do not inhale mist or vapor. NO SMOKING. If normal use of material presents a respiratory hazard, use only adequate ventilation or wear an appropriate respirator. Open containers slowly to control possible pressure release. Wash contaminated clothing and shoes thoroughly before reuse.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

7.2 Conditions for safe storage, including any incompatibilities

Store in dry, cool, well-ventilated areas away from incompatible materials (see Section 10.5), food and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder grind or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep locked up and out of reach of children.

7.3 Specific end uses

Apart from the uses mentioned in Section 1.2, no other specific uses are stipulated.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Occupational exposure limit values

CAS Number	Ingredient	OSHA PEL	ACGIH TLV	NIOSH
67-64-1	Acetone	1,000 ppm; 2,400 mg/m ³ TWA	500 ppm TWA 750 ppm STEL	250 ppm; 590 mg/ m ³ TWA 2,500 ppm IDLH
111-76-2	2-Butoxyethanol	50 ppm; 240 mg/m ³ TWA	20 ppm; 97 mg/m ³ TWA; Skin	50 ppm; 24 mg/ m ³ TWA 700 ppm IDLH; Skin
68410-97-9	Distillates (petroleum), hydrotreated light, low-boiling	-----	200 ppm - 8 h TWA	-----
67-56-1	Methanol	200 ppm; 250 mg/m ³ TWA	200 ppm; 160 mg/m ³ TWA 250 ppm; 327 mg/m ³ STEL Skin	200 ppm; 280 mg/ m ³ TWA 250 ppm; 325 mg/m ³ STEL 6,000 ppm IDLH; Skin
108-88-3	Toluene	200 ppm TWA	20 ppm TWA	100 ppm; 375 mg/m ³ TWA 150 ppm; 560 mg/m ³ STEL 500 ppm IDLH

A "skin" notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material, including eyes and mucous membranes, either by direct contact with vapors or by direct skin contact. It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposure should be considered.

8.2 Exposure controls

Engineering measures: Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. Use adequate ventilation. Local exhaust is preferable. Refer to Section 7.1.

Individual protection measures: Wear protective clothing to prevent repeated or prolonged contact with product. Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the representative supplier.

Hygiene measures: Facilities storing or using this material should be equipped with an eyewash station and safety shower. Change contaminated clothing. Preventive skin protection is recommended. Wash hands thoroughly after use, before eating, drinking, smoking or using the lavatory.

Eye/face protection: Wear safety glasses with unperforated side shields or chemical splash goggles during use.

Hand protection: Wear butyl rubber gloves or those recommended by glove supplier for protection against materials in Section 3. Gloves should be impermeable to chemicals and oil. Breakthrough time of selected gloves must be greater than the intended use period.

Skin protection: Wear protective clothing. Wear protective boots if the situation requires.

Respiratory protection: Always use an approved respirator when vapor/aerosols exceed permissible exposure limits. Where risk assessment shows air-purifying respirators are appropriate use a half-mask respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Environmental exposure controls: Do not empty into drains.

PPE must not be considered a long-term solution to exposure control. PPE usage must be accompanied by employer programs to properly select,

maintain, clean fit and use. Consult a competent industrial hygiene resource to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.



SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Clear, colorless liquid
Odor	Characteristic
Odor Threshold	No data available
Molecular Weight	Not applicable
Chemical Formula	Not applicable
pH	No data available
Freezing/Melting Point	No data available
Boiling Point Range	64.5 - 171 °C (148 - 340 °F)
Evaporation Rate	No data available
Flammability (solid, gas)	Not applicable
Flash Point	> -18 °C (> -0.4 °F) [estimated]
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Lower Explosive Limit (LEL)	No data available
Upper Explosive Limit (UEL)	No data available
Vapor Pressure	No data available
Vapor Density	No data available
Specific Gravity	0.7720 [calculated]
Density	0.767 - 0.777 g/ml (6.36 - 6.48 lb/gal) [calculated]
Viscosity	No data available
Solubility in Water	No data available
Partition Coefficient (n-octanol/water)	$\log P_{ow} = -0.82 - 6$
Oxidizing Properties	Not applicable
Explosive Properties	Not applicable
Volatiles by Weight @ 21 °C	No data available

9.2 Other Data

Flammability Classification	IB
-----------------------------	----

SECTION 10 – STABILITY AND REACTIVITY

10.1 Reactivity

This material is stable under normal handling conditions and use.

10.2 Chemical Stability

This material is stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air. Hazardous polymerization will not occur.

10.4 Conditions to avoid

Avoid high temperatures, sources of ignition, hot surfaces and contact with incompatible materials.

10.5 Incompatible materials

Strong oxidizing agents, strong acids, acid anhydrides, halogenated compounds, perchlorates, aliphatic amines

10.6 Hazardous decomposition products

Thermal decomposition products include oxides of carbon, hydrocarbons/hydrocarbon fragments, toxic fumes and gases.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute oral toxicity

LD₅₀, rat: 2,012 - 3,690 mg/kg [calculated]

Acute inhalation toxicity

LC₅₀, rat: >33.1 mg/l, 4 h [calculated]

Acute dermal toxicity

LD₅₀, rabbit: >4,000 mg/kg [calculated]

Skin irritation

Causes skin irritation.

Eye irritation

Causes serious eye irritation.

Sensitization

No data available

Carcinogenicity

No data available

Germ cell mutagenicity

No data available

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Specific organ toxicity - single exposure

May cause respiratory irritation, drowsiness or dizziness. May cause damage to the central nervous system, optic nerve, liver and kidneys.

Specific organ toxicity - repeated exposure

Causes damage to the central nervous and cardiovascular systems, optic nerve, liver and kidneys through prolonged and repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters the airways.

11.2 Further information

Reports have associated repeated and prolonged occupational exposure to **light petroleum products** with irreversible brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Fetotoxic effects have been observed in the offspring of laboratory animals when exposed to high doses of **Acetone** (CAS #67-64-1).

2-Butoxyethanol (CAS #111-76-2): IARC Group 3 carcinogen - Not classifiable as to its carcinogenicity to humans. Not listed as a carcinogen by ACGIH, NTP or OSHA. In long-term animal studies with 2-butoxyethanol, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans.

In animals, hemolysis (red blood cell breakage) and secondary effects to the kidneys and liver have been reported. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.

2-Butoxyethanol inhalation exposure in laboratory animals has been found to reduce body weight gain and food consumption in addition to hemolysis. After exposure was discontinued, these effects in animals disappeared. Adverse reproductive or birth effects were not reported in animals except when exposures were high enough to cause significant maternal toxicity.

Distillates (Petroleum), Hydrotreated Light (CAS #68410-97-9) is suspected of damaging fertility and the unborn child. Adverse symptoms of exposure may include reduced fetal weight, increased fetal mortality rate and skeletal malformations.

Methanol (CAS #67-56-1) is slowly eliminated from the body; therefore, it can have cumulative toxicity effects with repeated exposures. Ingestion of 100 - 125 ml (3 - 4 oz.) can be fatal or cause serious, irreversible injury such as blindness. May cause liver disorders (e.g. edema, proteinuria) and damage. Significant exposure to methanol may adversely affect people with chronic disease of the respiratory system, central nervous system, kidneys, liver, skin and/or eyes.

Methanol is a potential hazard to the fetus. Developmental effects have been observed in the offspring of rats and mice exposed to methanol by inhalation. These included skeletal, cardiovascular, urinary system and central nervous system (CNS) malformations in rats and increased resorptions and skeletal and CNS malformations in mice.

Toluene (CAS #108-88-3): IARC, Group 3 carcinogen - *Not classifiable as to its carcinogenicity to humans*. Not listed as a carcinogen by ACGIH, NTP or OSHA. Breathing high levels of toluene during pregnancy has been shown to result in children with birth defects and to retard mental abilities and growth. There is evidence that exposure to toluene at work is associated with spontaneous abortion.

Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Several studies of workers suggest long-term exposure may be related to small increases in spontaneous abortions and changes in some gonadotropic hormones. However, the weight of the evidence does not indicate toluene is a reproductive hazard to humans. Studies in laboratory animals indicate some changes in reproductive organs following high levels of exposure, but no significant effects on mating performance or reproduction were observed. In an epidemiologic study of toluene and pregnancy, occupational exposures to toluene were said to be associated with an increased incidence of renal, urinary, gastrointestinal and cardiac anomalies. Fetotoxicity (reduced fetal weight), behavioral effects (effects of learning and memory) and hearing loss (in males) were observed in the offspring of rats exposed to inhalation of toluene, in the absence of maternal toxicity.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Toxicity

This product is toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

This product is expected to biodegrade over time.

12.3 Bioaccumulation potential

Distillates (petroleum), hydrotreated light, low boiling have the potential to bioaccumulate.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other effects

Additional ecological information

Do not allow material to run into surface waters, wastewater or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Methods of disposal: The generation of waste should be avoided or minimized whenever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

RCRA F-Series: No listings above the reportable threshold (de minimis)

RCRA U-Series: Acetone (CAS #67-64-1), U002 Methanol (CAS #67-56-1), U154 Toluene (CAS #108-88-3), U220

SECTION 14 – TRANSPORTATION INFORMATION

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

For **UN1263** limited quantity for flammable liquids in Packing Group II when inner packagings are not over 5.0 liters (1.3 gallons) net capacity each, packed in a strong outer packaging.

For **UN1992** limited quantity for flammable liquids in Packing Group II when inner packagings are not over 1.0 liter (0.3 gallons) net capacity each, packed in a strong outer packaging.

USA DOT (Ground Transportation) - Bulk and Non-bulk

Proper Shipping Name	Paint related material
Hazard Class	3
UN	UN1263
Packing Group	II
NAERG	Guide #128
Packaging Authorization	Non-Bulk: 49 CFR 173.173; Bulk: 173.242
Packaging Exceptions	49 CFR 173.150; 49 CFR 172.102, special provision 149

IMO/IMDG (Water Transportation)

Proper Shipping Name	Flammable liquids, toxic n.o.s. (Methanol, Acetone)
Hazard Class	3 (6.1)
UN	UN1992
Packing Group	II
Marine Pollutant	No
EMS Number	F-E, S-D

ICAO/IATA (Air Transportation)

Proper Shipping Name	Flammable liquids, toxic n.o.s. (Methanol, Acetone)
Hazard Class	3 (6.1)
UN	UN1992
Packing Group	II
Quantity Limitations	49 CFR 175.27 and 175.75 - Cargo Aircraft Only: 60 l; Passenger Aircraft: 1 l

RID/ADR (Rail Transportation)

Proper Shipping Name	Paint related material
Hazard Class	3
UN	UN1263
Packing Group	II

Placard(s)



Class 6 placard for use with UN1992

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for substance or mixture

U. S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.-1200.

OSHA Process Safety Management Standard: This product is not regulated under OSHA PSM Standard 29 CFR 1910.119.

EPA Risk Management Planning Standard: This product is not regulated under EPA RMP Standard (RMP) 40 CFR Part 68.

EPA Federal Insecticide, Fungicide and Rodenticide Act: This product is not a registered Pesticide under the FIFRA, 40 CFR Part 150.

Toxic Substance Control Act (TSCA) Inventory: All substances in this product are listed on the TSCA Inventory. This product is not subject to TSCA 12(b) Export Notification.

Drug Enforcement Administration (DEA) List 2, Essential Chemicals (21 CFR 1310.02(b)) and 1310.4(f)(2)) and Chemical Code Number:
No listings

Drug Enforcement Administration (DEA) Lists 1 & 2, Exempt Chemical Mixtures (21 CFR 1310.12(c)) and Code Number

Acetone (CAS #67-64-1): List 2, DEA Chemical code 6532 - 35% by Weight or Volume; exports only; limit applies to acetone or any combination of acetone, ethyl ether, 2-butanone, methyl isobutyl ketone, and toluene if present in the mixture by summing the concentrations for each chemical.

Toluene (CAS #108-88-3): DEA Chemical code 6594 - 35% by Weight or Volume; exports only; limit applies to toluene or any combination of acetone, ethyl ether, 2-butanone, methyl isobutyl ketone, and toluene if present in the mixture by summing the concentrations for each chemical.

Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (CFATS) Chemicals: No listings

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories

Highly flammable liquid and vapor	May cause drowsiness or dizziness
Toxic if swallowed, inhaled or in contact with skin	Suspected of damaging fertility and the unborn child
May be fatal if swallowed and enters airways	May cause damage to organs (single exposure)
Causes skin irritation and serious eye irritation	May cause damage to organs through prolonged and repeated exposure

SARA 313 Information: Glycol Ethers (SARA code N230), Methanol, and Toluene are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: This material does not contain any substances that are subject to the reporting levels established by these sections of Title III of SARA.

SARA 302/304 Emergency Planning & Notification: This material does not contain any substances that are subject to the reporting levels established by these sections of Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains the following CERCLA reportable substances:

<i>Acetone</i> (CAS #67-64-1): RQ = 2,268 kg (5,000 lb)	<i>Toluene</i> (CAS #108-88-3): RQ = 454 kg (1,000 lb)
<i>Methanol</i> (CAS #67-56-1): RQ = 2,268 kg (5,000 lb)	

2-Butoxyethanol is a Glycol Ethers. There is no RQ assigned to this broad class, although the class is a CERCLA hazardous substances. Refer to 50 Federal Register 13456 (April 4, 1985).

This product has a Reportable Quantity (RQ) of 56,346 lbs. (7,760.6 gal) based on the RQ for *toluene* of 1,000 lb. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Clean Air Act (CAA)

Glycol Ethers (EDF 109), Methanol and Toluene are Hazardous Air Pollutants (HAPs) designated in CAA Section 112 (b):

This product does not contain Class 1 Ozone depleters.

This product does not contain Class 2 Ozone depleters.

Clean Water Act (CWA)

Glycol Ethers (EDF 109), Methanol and Toluene are Hazardous Substances.

Toluene is a Priority Pollutant.

Toluene is a Toxic Pollutant.

Distillates (petroleum) hydrotreated light low boiling are classified as an oil under Section 311 of the CWA and the Oil Pollution Act (OPA) of 1990.

U.S. State Regulations

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

 **WARNING:** This product will expose you to *Methanol* and *Toluene*, which are known to the state of California to cause birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other U.S. State Inventories

Acetone (CAS #67-64-1) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, ME, MA, MN, NJ, NY, PA, RI, WA.

2-Butoxyethanol (CAS #111-76-2) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, MN, PA, RI, WI.

Methanol (CAS #67-56-1) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, IL, ME, MA, MN, NJ, NY, NC, PA, RI, WA.

Toluene (CAS #108-88-3) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, IL, ME, MA, MI, MN, NJ, NY, NC, PA, RI, WA, WI.

Canada

WHMIS Hazard Classification

Highly flammable liquid and vapor	May cause respiratory irritation, drowsiness or dizziness
May be fatal if swallowed and enters airways	Suspected of damaging fertility or the unborn child
Toxic if inhaled, swallowed or in contact with skin	May cause damage to organs through prolonged or repeated exposure
Causes skin irritation and serious eye irritation	

Canadian National Pollutant Release Inventory (NPRI): Acetone, 2-Butoxyethanol and Toluene are listed on the NPRI.

European Economic Community

WGK, Germany (Water danger/protection): 3 (severe hazard to waters)

Global Chemical Inventory Lists

Country	Inventory Name	Listed
Canada	Domestic Substance List (DSL)	Yes
Canada	Non-Domestic Substance List (NDSL)	No
Europe	Inventory of New and Existing Chemicals (EINECS)	Yes
United States	Toxic Substance Control Act (TSCA)	Yes
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
New Zealand	New Zealand Inventory of Chemicals (NZIoC)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (KECI)	Yes
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Yes

*Yes - All components of this product comply with the inventory requirements administered by the governing country.

No - One or more components of this product are not on the inventory or are exempt from listing.

15.2 Chemical safety assessment

A chemical safety assessment was not carried out for this product.

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		C

C = safety glasses, gloves and an apron

HMIS Hazard Rating Legend

0 = Minimal 1 = Slight 2 = Moderate

3 = Serious 4 = Severe


* = Chronic Health Hazard

NFPA Hazard Rating Legend

0 = Insignificant 1 = Slight 2 = Moderate

3 = High 4 = Extreme

National Fire Protection Association (NFPA)



Full Text of GHS Hazard Phrases Referenced in Section 3 (not covered in Section 2)

H227 - Combustible liquid

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H332 - Harmful if inhaled

Abbreviation Key

ACGIH	American Conference of Governmental Industrial Hygienists	LD _{Lo}	Lowest Lethal Dose
ADR	Accord Dangereux Routier (European regulations concerning the international transport of dangerous goods by road)	mppcf	Millions of Particles Per Cubic Foot
CAS	Chemical Abstract Services	NA	North America
CFR	Code of Federal Regulations	NAERG	North American Emergency Response Guide Book
COC	Cleveland Open Cup	NIOSH	National Institute for Occupational Safety & Health
DOT	Department of Transportation	NTP	National Toxicology Program
EC ₅₀	Half maximal effective concentration	OSHA	Occupational Safety and Health Administration
EMS	Emergency Response Procedures for Ships Carrying	PBT	Persistent, Bioaccumulating and Toxic
EPA	Environmental Protection Agency	PEL	Permissible exposure limit
ErC ₅₀	Reduction of Growth Rate	PMCC	Pensky-Martens Closed Cup
ERG	Emergency Response Guide Book	ppm	Parts Per Million
FDA	Food and Drug Administration	RCRA	Resource Conservation and Recovery Act
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS)	RID	Dangerous Goods by Rail
HCS	Hazard Communication Standard	RQ	Reportable Quantity
IARC	International Agency for Research on Cancer	TCC/Tag	Tagliabue Closed Cup
IATA	International Air Transport Association	TLV	Threshold Limit Value
IC ₅₀	Half Maximal Inhibitory Concentration	TSCA	Toxic Substance Control Act
ICAO	International Civil Aviation Organization	TWA	Time-weighted Average
IDLH	Immediately Dangerous to Life and Health	UN	United Nations
IMDG	International Maritime Dangerous Goods	VOC	Volatile Organic Compounds
IMO	International Maritime Organization	vPvB	Very Persistent and Very Bioaccumulating
LC ₅₀	50% Lethal Concentration	WHMIS	Workplace Hazardous Materials Information System
LD ₅₀	50% Lethal Dose		

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented, and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume damage or expense arising out of or in any way responsibility and expressly disclaim liability.

for loss, connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.

Revision date: 05 June 2023, Version 2

Supersedes SDS: 01 August 2019, Version 1

<end of document>