

FRONT LABEL



BACK LABEL

OIL BOND™ Latex Paint Additive

Crown® Latex Agent™

- For use on previously painted oil-based surfaces, including polyurethane (not recommended for plastic surfaces)
- Cleans and deglosses in one easy step, without the need to sand or prime Will not affect the qualities of latex paint

Contains Surfactant. Avoid breathing vapors. Avoid contact with the eyes, skin and clothing. Use only with adequate ventilation. Wash throughly after handling. Keep container dosed when not in use. Refer to Safety Data Sheet (SDS) at www.crownbrand.com for additional cautions before using, transporting or storing this product.

KEEP OUT OF REACH OF CHILDREN

FIRST AID: Eye Contact: Immediately flush eyes with water for at least 15 minutes and call a physician. Skin Contact: Wash thoroughly with sapa and water, Get medical attention if irritation persists. Inhalation: Nove to fresh air, Get medical attention if irritation or other symptoms develop and persist. Ingestion: Do not induce vomiting unless directed to do so by medical personnal. Never give anything by mouth to an unconscious or drowsy person. Immediately call a physician or poison control center,

DISPOSAL: All waste materials should be disposed of in accordance with local, state and federal regulations. WARRANTY: Satisfaction guaranteed. Supplier's warranty is limited to replacement of this Product if the Product is found to be defective.

KEEP CONTAINERS CLOSED TIGHTLY AFTER EACH USE DO NOT TRANSFER CONTENTS TO UNLABELED CONTAINERS

DO NOT REUSE CONTAINER
DO NOT STORE IN DIRECT SUNLIGHT

Becyclable —





PATENT PENDING MADE IN THE USA

DIRECTIONS

- 1. SHAKE WELL FOR AT LEAST 30 SECONDS
- 2. PRETREAT SURFACE This will effectively clean, degloss and assist adhesion of the latex paint to the project surface. Apply the Oil Bond product to a clean, lint free cotton rag and wipe the surface with a moderate amount of product. Regularly reapply the product onto fresh, clean areas of the rag and change rags as dirt is absorbed onto the rag. Appropriate gloves are recommended. After pretreating, allow the surface to dry for one hour.
- 3. ADD TO LATEX PAINT Begin by adding 16 oz. of the Oil Bond latex paint additive to one gallon of latex paint. Stir well. Apply the latex paint with Oil Bond additive to project surface using brush, roller or spray in the first coat of paint. Additional coats do not require the Oil Bond additive. Allow to dry as directed by the latex paint instructions. Full cure of the paint may take a day or two, depending on the conditions (temperature, humidity, etc.) The coating will be the toughest after 2-3 days and should completely harden within about one week.

NOTE: If the color from project surface begins to transfer onto the rag or the finish begins to loosen from the surface during pretreatment, then pretreating with a socuring pad is necessary (using a multipunces primer may be used to avoid bleeding). If a smooth surface is not achieved after pretreating, the surface will need to be sanded and primed.

NOTE: For use in spray equipment - Add the Latex paint with Oil Bond additive as directed and dilute as necessary with extra water to meet the viscosity requirement for your spray equipment per the manufacturer's directions. It is the user's responsibility to determine whether this product suits the ourroose of the user's acolication.

SolvChem, Inc. Pearland, Texas 77581 www.latexagent.com www.crownbrand.com

V.O.C. COMPLIANT <3% V.O.C. by weight 2020 - Crown is a registered trademark of SolvChem., Inc.



PMS 7416

Black

PMS 7543 PRINTS ON WHITE LABEL STOCK





PRINTS ON WHITE LABEL STOCK