

## How to Remove Existing Caulk

### PLEASE NOTE:

Always test a small inconspicuous area of the surface around old caulk first using a tiny bead of Crown® TuffStrip® Caulk Remover. Not for use on painted surfaces or on coatings made from acrylic, fiberglass, epoxy, plastics, or composites. Follow the directions below.

### DIRECTIONS:

1. Do not use on acrylic, fiberglass, epoxy, plastic, or composite surfaces.
2. Shake vigorously for 15-20 seconds before use.
3. Apply a thin layer of Crown TuffStrip Caulk Remover, covering the existing caulk completely.
4. Let set for 2 hours and monitor closely for caulk remover dripping. If dripping occurs, wipe up runoff immediately with a wet cloth towel.
5. Remove the loosened caulk with a caulk removing tool or putty knife. If the caulk is not easily removed, let it sit another hour and try again.
6. Clean surface with water, and let surface dry completely before re-caulking.
7. Not following directions will void any warranties.

### NOTE:

- Do not store in freezing temperatures.
- Do not let Crown Caulk Remover come in contact with coated and painted surfaces as damage may occur. Wipe up drips immediately with a wet towel.

### SURFACE COVERAGE:

One bottle of Crown Caulk Remover removes up to 47 linear feet of caulk.

 **WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

 **TUFFSTRIP®** 



# CAULK REMOVER



**SOFTENS OLD CAULK  
FOR EASY REMOVAL**

**REMOVES ALL CAULKS  
INCLUDING SILICONES**

**CLINGS TO  
VERTICAL SURFACES**

**16 FL OZ (473 mL)**

Contains Dimethyl Esters.

### KEEP OUT OF REACH OF CHILDREN

May cause eye and skin irritation. Avoid contact with eyes, skin and clothing. Wash hands after use. Wear gloves when using this product. Refer to Safety Data Sheet (SDS) at [www.crownbrand.com](http://www.crownbrand.com) for additional cautions before using, transporting or storing this product.

**FIRST AID: Eye Contact:** Flush with water. Call a physician if irritation persists. **Skin Contact: contact:** wash with soap and water.

**Ingestion:** Do not induce vomiting. Call a physician or poison center.

Supplier's warranty is limited to replacement of this Product if the Product is found to be defective.

CARB Product Category:  
General Adhesive Remover  
<20% V.O.C. by weight

Not hazardous in accordance with the OSHA Hazard Communication Standard, 29CFR1910.1200-2012.

Distributed by  
**SolvChem., Inc.**  
1904 Mykawa Road,  
Pearland, Texas 77581  
**MADE IN USA**

©2020 SolvChem, Inc. All Rights Reserved

