

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: Crown Xylol

SDS number: CR.XY

Synonym(s): Xylol; Xylenes; Xylene isomers and ethylbenzene; Dimethylbenzenes and ethylbenzene

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Solvent, fuel, feedstock; use only in well ventilated areas

Uses advised against: No data available

1.3 Details of the supplier and of the safety data sheet

SolvChem Consumer Products

1904 Mykawa Road

Pearland, TX 77581-3210 USA

1-281-485-1458

1.4 Emergency telephone number

CHEMTREC: 1-800-424-9300 (USA)

CANUTEC: 1-613-996-6666 (Canada)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification in accordance with 29 CFR 1910 (OSHA HCS) and Regulation EC No. 1272/2008

Flammable Liquid - Category 3 [H226]

Acute Toxicity, Oral - Category 5 [H303]

Aspiration Hazard - Category 1 [H304]

Acute Toxicity, Dermal - Category 4 [H312]

Skin Irritation - Category 2 [H315]

Acute Toxicity, Inhalation - Category 4 [H332]

Specific Organ Toxicity, Single Exposure - Category 3; STOT SE 3 [H335]

Specific Target Organ Toxicity, Repeated Exposure - Category 2; STOT RE 2 [H373]

2.2 Label elements

Hazard symbol(s):



GHS02



GHS07



GHS08

Signal word:

Danger

Hazard statement(s):

H226 - Flammable liquid and vapor

H303 - May be harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H373 - May cause damage to the auditory system through prolonged and repeated exposure

Precautionary statements

[Prevention]

P210 - Keep away from heat, open flames and hot surfaces. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 + P242 - Use explosion proof electrical, ventilating and lighting equipment. Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe fumes, mist and vapor.

P264 - Wash hands and other exposed skin areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing and eye protection.

[Response]

P301 + P331 + P310 - IF SWALLOWED: DO NOT induce vomiting. Immediately call a POISON CENTER or doctor.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 + P312 - IF INHALED: Remove victim to fresh air and keep at rest in a comfortable position for breathing. Call a POISON CENTER or doctor if you feel unwell.

P321 - Specific treatment: Call a POISON CENTER or doctor if you feel unwell. Refer to Section 4 of this SDS.

P332 + P313 - If skin irritation occurs: Get medical attention.

[Storage]
[Disposal]

P362 - Take off contaminated clothing and wash before reuse.
P370 + P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P405 + P403 + P233 + P235 - Store locked up in a well-ventilated place. Keep container tightly closed. Keep cool.
P501 - Dispose of contents and containers in accordance with national and local regulations.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Suspected of causing cancer. Repeated exposure may cause skin dryness or cracking.

2.4 Unknown acute toxicity (US)

Not applicable

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

% by Weight	Ingredient	CAS Number	EC Number	Index Number	GHS Classification
60 - 100	Xylene	1330-20-7	215-535-7	601-022-00-9	H226, H312, H315, H332
10 - 30	Ethylbenzene	100-41-4	202-849-4	601-023-00-4	H225, H304, H332, H373
0.1 - 1.0	Cumene	98-82-8	202-704-5	601-024-00-X	H226, H304, H335, H411

There are no additional ingredients present in this product which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4 – FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation: If product mist or vapor causes respiratory irritation or distress, move the exposed person to fresh air immediately. If breathing is difficult or irregular, administer oxygen; if respiratory arrest occurs, start artificial respiration by trained personnel. If unconscious, maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If symptoms persist or if the victim feels unwell, seek medical attention.

Eyes: Immediately flush eyes with large amounts of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses if present and easy to do after first 2 minutes and continue rinsing. If irritation persists seek medical attention, preferably from an ophthalmologist.

Skin: Flush skin with large amounts of water while removing contaminated clothing. Wash the affected area with soap and water followed by thorough rinsing. Wash contaminated clothing and shoes before reuse. If irritation persists, seek medical attention.

Ingestion: Rinse mouth with water if the victim is conscious. Remove dentures if present. DO NOT induce vomiting unless directed to do so by medical personnel. Vomiting may occur spontaneously. To prevent aspiration of material into the lungs, lay the victim on one side with the head lower than the waist. Never give anything by mouth to an unconscious or convulsing person. Do not leave the victim unattended. Seek immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Potential health symptoms and effects

Eyes: Causes eye irritation with inflammation, discomfort, tearing and blurred vision. Vapor or mist can cause eye irritation.

Skin: Causes skin irritation with localized redness, itching and discomfort. Prolonged contact with unprotected skin may cause defatting of the skin and dermatitis. Prolonged contact may cause chemical burns and blistering. Harmful if absorbed through the skin.

Inhalation: Harmful if inhaled. May cause respiratory tract irritation with headache, cough and shortness of breath. May cause nausea, vomiting, drowsiness, dizziness, anesthetic effects, narcosis, fatigue, cyanosis, apnea and cardiac arrest. May cause central nervous system depression and other central nervous system effects including incoordination, impaired mental and physical abilities, speech impairment, unconsciousness, coma and death. Lung irritation may lead to chemical pneumonitis and pulmonary edema. May cause reversible liver and kidney damage.

Ingestion: Harmful if swallowed. Causes irritation of the digestive tract with nausea, vomiting, abdominal pain and diarrhea. May cause central nervous system depression characterized by excitement, followed by headache, dizziness, drowsiness and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. May cause reversible liver and kidney damage. This material can get into the lungs during swallowing or vomiting causing lung inflammation and chemical pneumonitis, which may be fatal. Symptoms of aspiration into the lungs include coughing, gasping, choking, shortness of breath, bluish colored skin, rapid breathing and rapid heart rate.

Chronic: Individuals with pre-existing skin conditions and respiratory disorders may be more susceptible to the effects of this product. Prolonged or repeated skin contact may cause defatting of the skin and dermatitis or aggravate existing skin conditions. Chronic exposure may cause reversible eye damage, dyspnea (labored breathing), confusion, dizziness, apprehension, memory loss, headache, tremors, weakness, anorexia, nausea, tinnitus, irritability, thirst, mild changes in liver function, kidney impairment, anemia and hyperplasia, but not destruction of the bone marrow. Effects may be delayed. Impaired central nervous system functions from pre-existing disorders may be aggravated by exposure to this product. Xylene is a confirmed animal carcinogen. Ethylbenzene and Cumene are possible human carcinogens. Exposure to this product may harm the unborn child. Refer to Section 11.2.

4.3 Indication of any immediate medical attention and special treatment needed

Advice to doctor and hospital personnel

If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider active charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable methods of extinction: Use extinguishing media such as water spray or fog, carbon dioxide, foam and dry chemical.

Unsuitable methods of extinction: Water jets or streams may spread the fire.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapor! Vapors are heavier than air and can travel along the ground to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Exposure to ignition sources (e.g., cell phones) can ignite vapors, causing a flash fire. Closed containers may explode due to the buildup of pressure when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent or may be delayed. Obtain medical attention.

Explosion hazards: Vapors may form an explosive mixture with air. Ground and bond containers in storage and when container is in use.

5.3 Advice to firefighters

Firefighters should wear full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. *Be aware that burning liquid will float on water.* Firefighters should control runoff to prevent environmental contamination. Notify appropriate authorities of potential fire and explosion hazard if liquid enters sewers or waterways.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate non-essential personnel. Wear appropriate protective clothing and equipment designated in Section 8.2. Ventilate the area. Remove all sources of ignition. NO SMOKING. Clean up spills immediately. Spill creates a slip hazard.

6.2 Environmental precautions

Avoid dispersal of spilled material or runoff and prevent contact with soil and entry into drains, sewers or waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements.

6.3 Methods and materials for containment and cleaning up

Approach spill from upwind direction. DO NOT FLUSH SPILL DOWN THE DRAIN. Cover drains and contain spill. Cover spill with a large quantity of inert absorbent. Do not use combustible material such as sawdust. Collect material using non-sparking tools and place into an approved container for proper disposal. Observe possible material restrictions (Sections 7.2 and 10.5). Do not allow material or runoff from rinsing contaminated areas to enter floor drains or storm drains and ditches that lead to waterways. Dispose of contents and containers via a licensed waste disposal contractor.

6.4 Reference to other sections

For indications about waste treatment, see Section 13.

SECTION 7 – STORAGE AND HANDLING

7.1 Precautions for safe handling

Wear all appropriate personal protective equipment specified in Section 8.2. Do not get in eyes or on skin or clothing. Do not inhale mist or vapor. NO SMOKING. If normal use of material presents a respiratory hazard, use only adequate ventilation or wear an appropriate respirator. Open containers slowly to control possible pressure release. Wash contaminated clothing and shoes thoroughly before reuse.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

7.2 Conditions for safe storage, including any incompatibilities

Store in dry, cool, well-ventilated areas away from incompatible materials (see Section 10.5), food and drink. Keep away from heat and ignition sources. Transfer only to approved containers having correct labeling. Keep containers tightly closed when not in use. Protect containers against physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Do not cut, drill, weld, braze, solder, grind, or perform similar operations on or near empty containers. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children.

7.3 Specific end uses

Apart from the uses mentioned in Section 1.2, no other specific uses are stipulated.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

CAS Number	Ingredient	OSHA PEL	ACGIH TLV	NIOSH
98-82-8	Cumene	50 ppm; 245 mg/m ³ TWA	50 ppm; 246 mg/m ³ TWA 400 ppm; 984 mg/m ³ STEL Skin	50 ppm; 245 mg/m ³ TWA; Skin 900 ppm IDLH [10% LEL]
100-41-4	Ethylbenzene	100 ppm, 435 mg/m ³ TWA	20 ppm; 87 mg/m ³ TWA	100 ppm, 435 mg/m ³ TWA 150 ppm, 545 mg/m ³ STEL 800 ppm IDLH

1330-20-7	Xylene	100 ppm; 245 mg/ m ³ TWA Skin	100 ppm; 435 mg/ m ³ TWA	100 ppm; 435 mg/ m ³ TWA 150 ppm; 545 mg/m ³ STEL 900 ppm IDLH
-----------	--------	---	-------------------------------------	--

A "skin" notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material, including eyes and mucous membranes, either by direct contact with vapors or by direct skin contact. It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposure should be considered.

8.2 Exposure controls

Engineering measures: Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. Use adequate ventilation. Local exhaust is preferable. Refer to Section 7.1.

Individual protection measures: Wear protective clothing to prevent repeated or prolonged contact with product. Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the representative supplier.

Hygiene measures: Facilities storing or using this material should be equipped with an eyewash station and safety shower. Change contaminated clothing. Preventive skin protection is recommended. Wash hands thoroughly after use, before eating, drinking, smoking or using the lavatory.

Eye/face protection: Wear safety glasses with unperforated side shields or protective splash goggles during use.

Hand protection: Wear gloves made of Nitrile rubber, polyvinyl alcohol (PVA) supported or those recommended by glove supplier for protection against materials in Section 3. Gloves should be impermeable to chemicals and oil. Breakthrough time of selected gloves must be greater than the intended use period.

Skin protection: Wear protective clothing. Wear protective boots if the situation requires.

Respiratory protection: Always use an approved respirator when vapor/aerosols exceed permissible exposure limits. Where risk assessment shows air-purifying respirators are appropriate use a half-mask respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Environmental exposure controls: Do not empty into drains.

PPE must not be considered a long-term solution to exposure control. PPE usage must be accompanied by employer programs to properly select, maintain, clean, fit and use. Consult a competent industrial hygiene resource to determine hazard potential and/or the PPE manufacturers to ensure adequate protection



SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Clear, colorless liquid
Odor	Sweet, pungent aromatic hydrocarbon
Odor Threshold	1 ppm (xylenes)
Molecular Weight	106.17 g/mol (xylenes)
Chemical Formula	C ₈ H ₁₀ (xylenes)
pH	No data available
Freezing/Melting Point	- 48 °C (- 54.4 °F)
Initial Boiling Point	138 °C (280.4 °F)
Evaporation Rate	0.8 [n-BuOAc = 1]
Flammability (solid, gas)	Not applicable
Flash Point	26.9 - 31.9 °C (80.42 - 89.42 °F), closed
Autoignition Temperature	cup 432 °C (809.6 °F)
Decomposition Temperature	No data available
Lower Explosive Limit (LEL)	1% (v)
Upper Explosive Limit (UEL)	7% (v)
Vapor Pressure	0.93 kPa (7 mm Hg), ambient
Vapor Density	3.7 [Air = 1]
Specific Gravity	0.87
Density	0.8687 g/ml (7.256 lb/gal)
Viscosity	No data available
Solubility in Water	Negligible
Partition Coefficient (n-octanol/water)	log P _{ow} = 3.12 - 3.2
Oxidizing Properties	Not applicable
Explosive Properties	Not applicable
Volatiles by Weight @ 21 °C	100%
VOC Content	100% (1,000 g/l) per CARB

9.2 Other Data

Flammability Classification

IC

SECTION 10 – STABILITY AND REACTIVITY

10.1 Reactivity

This material is stable under normal handling conditions and use.

10.2 Chemical Stability

This material is stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air. Reacts with strong oxidizing agents. Hazardous polymerization will not occur.

10.4 Conditions to avoid

High temperatures, sources of ignition, hot surfaces, contact with incompatible materials. Avoid impact. Avoid use in confined areas.

10.5 Incompatible materials

Strong oxidizing agents, strong reducing agents, strong acids, alkalis, rubber, various plastics

10.6 Hazardous decomposition products

Thermal decomposition products include oxides of carbon and hydrocarbons.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute oral toxicity

LD₅₀, rat: > 3,817 mg/kg [calculated]

Acute inhalation toxicity

LC₅₀, rat: > 23,393 mg/m³ [calculated]

Acute dermal toxicity

LD₅₀, rabbit: > 10,004 mg/kg [calculated]

Skin irritation

Causes mild skin irritation.

Eye irritation

Causes eye irritation.

Sensitization

No data available

Carcinogenicity

Suspected of causing cancer.

Germ cell mutagenicity

No data available

Reproductive toxicity

No data available

Specific organ toxicity - single exposure

May cause respiratory irritation, drowsiness or dizziness.

Specific organ toxicity - repeated exposure

Causes damage to the auditory system through prolonged and repeated use.

Aspiration hazard

May be fatal if swallowed and enters the airways.

11.2 Further information

Cumene (CAS #98-82-8): IARC, Group 2B carcinogen - *Possibly carcinogenic to humans*; NTP - *Reasonably anticipated to be a human carcinogen*. Not listed as a carcinogen by ACGIH or OSHA.

Ethylbenzene (CAS #100-41-4): IARC, Group 2B carcinogen - *Possibly carcinogenic to humans*; ACGIH, A3 - *Confirmed animal carcinogen with unknown relevance to humans*. Not listed as a carcinogen by NTP or OSHA. Ethylbenzene may have teratogenic effects based upon results of laboratory experiments.

Xylene (CAS #1330-20-7): IARC, Group 3 carcinogen - *Not classifiable as to its carcinogenicity to humans*. ACGIH, A4 - *Not classifiable as a human carcinogen*. Not listed as a carcinogen by NTP or OSHA. Xylene is a confirmed animal carcinogen. It is a developmental hazard and may harm the unborn child based on animal information. It has been associated with low birth weight or size and learning disabilities.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Toxicity

Large spills or discharges may be harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

This material is expected to be biodegradable.

12.3 Bioaccumulation potential

The bioaccumulation potential for this product is low.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This material does not contain substances that are persistent, bioaccumulative, and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

12.6 Endocrine disrupting properties

This mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other effects

Additional ecological information

Do not allow material to run into surface waters, wastewater or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Methods of disposal: The generation of waste should be avoided or minimized whenever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

RCRA R-Series: Xylene (CAS #1330-20-7), D001

RCRA U-Series: Xylene (CAS #1330-20-7), U239

SECTION 14 – TRANSPORTATION INFORMATION

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

Limited quantity for flammable liquids in Packing Group III when inner packagings are not over 5.0 liters(1.3 gallons) net capacity each, packed in a strong outer packaging.

USA DOT (Ground Transportation) - Bulk and Non-bulk

Proper Shipping Name	Xylenes
Hazard Class	3
UN/NA	UN1307
Packing Group	III
NAERG	Guide #130
Packaging Authorization	Non-Bulk: 49 CFR 173.202; Bulk: 173.242
Packaging Exceptions	49 CFR 173.150

IMO/IMDG (Water Transportation)

Proper Shipping Name	Xylenes
Hazard Class	3
UN/NA	UN1307
Packing Group	III
Marine Pollutant	No
EMS Number	F-E, S-D

ICAO/IATA (Air Transportation)

Proper Shipping Name	Xylenes
Hazard Class	3
UN/NA	UN1307
Packing Group	III
Quantity Limitations	49 CFR 175.27 and 175.75 - Cargo Aircraft Only: 60 l; Passenger Aircraft: 5 l

RID/ADR (Rail Transportation)

Proper Shipping Name	Xylenes
Hazard Class	3
UN/NA	UN1307
Packing Group	III

Placard(s)



SECTION 15 - REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for substance or mixture

U. S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

OSHA Process Safety Management Standard: This product is not regulated under OSHA PSM Standard 29 CFR 1910.119.

EPA Risk Management Planning Standard: This product is not regulated under EPA RMP Standard (RMP) 40 CFR Part 68.

EPA Federal Insecticide, Fungicide and Rodenticide Act: This product is not a registered Pesticide under the FIFRA, 40 CFR Part 150.

Toxic Substance Control Act (TSCA) Inventory: All substances in this product are listed on the TSCA Inventory. This product is not subject to TSCA 12(b) Export Notification.

Drug Enforcement Administration (DEA) List 2, Essential Chemicals (21 CFR 1310.02(b)) and 1310.4(f)(2)) and Chemical Code Number
No listings

Drug Enforcement Administration (DEA) Lists 1 & 2, Exempt Chemical Mixtures (21 CFR 1310.12(c)) and Code Number: No listings

Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (CFATS) Chemicals: No listings

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories

Flammable liquid and vapor	Causes skin irritation
May be harmful if swallowed	May cause drowsiness or dizziness
May be fatal if swallowed and enters airways	Suspected of causing cancer
Causes skin irritation and serious eye irritation	May cause damage to organs through prolonged and repeated exposure
Harmful if inhaled and in contact with skin	May cause cancer [HNOC]

SARA 313 Information: Cumene, Ethylbenzene and Xylene are subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: None of the components of the product exceed the threshold (de minimis) reporting levels of established by these sections of Title III of SARA.

SARA 302/304 Emergency Planning & Notification: None of the components of the product exceed the threshold (de minimis) reporting levels established by of these sections of Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains the following CERCLA reportable substances:

Cumene (CAS #98-82-8): RQ - 2,268 kg (5,000 lb)	Xylene (CAS #1330-20-7): RQ - 45.4 kg (100 lb)
Ethylbenzene (CAS #100-41-4): RQ - 454 kg (1,000 lb)	

This product has a Reportable Quantity (RQ) of 124.3 lb (17.2 gal) based on the RQ for *xylene* of 100 lb. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Clean Air Act (CAA)

Cumene, Ethylbenzene and Xylene are Hazardous Air Pollutants (HAPs) designated in CAA Section 112 (b).

This product does not contain Class 1 Ozone depleters.

This product does not contain Class 2 Ozone depleters.

Clean Water Act (CWA)


Cumene and Ethylbenzene are Hazardous Substances.

This product does not contain Priority Pollutants.

This product does not contain Toxic Pollutants.

U.S. State Regulations

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

 **WARNING:** This product will expose you to *Cumene* and *Ethylbenzene*, which are known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Other U.S. State Inventories

Cumene (CAS #98-82-8) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, IL, MA, MN, NJ, NY, PA, RI, WA, WV, WI.

Ethylbenzene (CAS #100-41-4) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, IL, ME, MA, MN, NJ, NY, PA, RI, WA, WI.

Xylene (CAS #1330-20-7) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, DE, ID, ME, MA, MN, NJ, NY, PA, RI, WA.

Canada

WHMIS Hazard Classification

Highly flammable liquid and vapor	May cause drowsiness or dizziness
May be fatal if swallowed and enters airways	Suspected of causing cancer
Causes skin irritation and serious eye irritation	May cause damage to organs through prolonged or repeated exposure

Canadian National Pollutant Release Inventory (NPRI): Cumene, Ethylbenzene and Xylene are listed on the NPRI.

European Economic Community

WGK, Germany (Water danger/protection): 2 (obviously hazardous to water)

Global Chemical Inventory Lists

Country	Inventory Name	Listed
Canada	Domestic Substance List (DSL)	Yes
Canada	Non-Domestic Substance List (NDSL)	No
Europe	Inventory of New and Existing Chemicals (EINECS)	Yes
United States	Toxic Substance Control Act (TSCA)	Yes
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
New Zealand	New Zealand Inventory of Chemicals (NZIoC)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (KECI)	Yes
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Yes

*Yes - All components of this product comply with the inventory requirements administered by the governing country.

No - One or more components of this product are not on the inventory or are exempt from listing or will require registration.

15.2 Chemical safety assessment

A chemical safety assessment was not carried out for this product.

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		C

C = safety glasses, gloves
& apron

HMIS Hazard Rating Legend

0 = Minimal 1 = Slight 2 = Moderate

3 = Serious 4 = Severe


* = Chronic Health Hazard

NFPA Hazard Rating Legend

0 = Insignificant 1 = Slight 2 = Moderate

3 = High 4 = Extreme

National Fire Protection Association (NFPA)



Full Text of GHS Hazard Phrases Referenced in Section 3 (not covered in Section 2)

H225 - Highly flammable liquid and vapor

H411 - Toxic to aquatic life with long lasting effects

Abbreviation Key

ACGIH	American Conference of Governmental Industrial Hygienists	LD _{Lo}	Lowest Lethal Dose
ADR	Accord Dangereux Routier (European regulations concerning the international transport of dangerous goods by road)	mppcf	Millions of Particles Per Cubic Foot
CAS	Chemical Abstract Services	NA	North America
CFR	Code of Federal Regulations	NAERG	North American Emergency Response Guide Book
COC	Cleveland Open Cup	NIOSH	National Institute for Occupational Safety & Health
DOT	Department of Transportation	NTP	National Toxicology Program
EC ₅₀	Half maximal effective concentration	OSHA	Occupational Safety and Health Administration
EMS	Emergency Response Procedures for Ships Carrying	PBT	Persistent, Bioaccumulating and Toxic
EPA	Environmental Protection Agency	PEL	Permissible exposure limit
ErC ₅₀	Reduction of Growth Rate	PMCC	Pensky-Martens Closed Cup
ERG	Emergency Response Guide Book	ppm	Parts Per Million
FDA	Food and Drug Administration	RCRA	Resource Conservation and Recovery Act
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS)	RID	Dangerous Goods by Rail
HCS	Hazard Communication Standard	RQ	Reportable Quantity
IARC	International Agency for Research on Cancer	TCC/Tag	Tagliabue Closed Cup
IATA	International Air Transport Association	TLV	Threshold Limit Value
IC ₅₀	Half Maximal Inhibitory Concentration	TSCA	Toxic Substance Control Act
ICAO	International Civil Aviation Organization	TWA	Time-weighted Average
IDLH	Immediately Dangerous to Life and Health	UN	United Nations
IMDG	International Maritime Dangerous Goods	VOC	Volatile Organic Compounds
IMO	International Maritime Organization	vPvB	Very Persistent and Very Bioaccumulating
LC ₅₀	50% Lethal Concentration	WHMIS	Workplace Hazardous Materials Information System
LD ₅₀	50% Lethal Dose		

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented, and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume damage or expense arising out of or in any way responsibility and expressly disclaim liability.

for loss, connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.

Revision date: 25 July 2024, Version 7

Supersedes SDS: 25 March 2021, Version 6

<end of document>